

3. To specify the actions and services that generate an audit record, select `sas.audit.record` in the definition list.

4. Click  **Edit**.

5. To specify whether entries are recorded from a specified application or service, select **+ Add property** in the **application** area.

In the Add Property window, specify the application or service in the **Name** field using the format `sas.audit.record.application.application.status`

- Valid values for *application* are *serviceName* values in the SAS Configuration Server. To obtain a list of all possible values, issue one of these commands:

Unix:

```
./sas-bootstrap-config catalog services | grep serviceName
```

Windows:

```
sas-bootstrap-config.exe catalog services | findstr serviceName
```

These commands return a list of *serviceName*s that you can use as values for *application*.

```
...
"serviceName": "SASStudioV",
"serviceName": "SASThemeDesigner",
"serviceName": "SASVisualAnalytics",
"serviceName": "alert-track",
"serviceName": "analyticsComponents",
"serviceName": "analyticsDataSegmentation",
...
```

- Valid values for *status* are *enabled* or *state*. Specify *enabled* to control whether audit records are enabled for the service. Specify *state* to specify the state when audit records are created.

Specify the value for the property in the **Value** field.

These are examples:

- Specify `sas.audit.record.application.identities.enabled` in the **Name** field and `false` in the **Value** field to disable recording of entries from the Identities service.
- Specify `sas.audit.record.application.SASLogin.state` in the **Name** field and `failure` in the **Value** field to disable recording of entries from the SASLogon service.

Configuration

The set of properties that are used to control how audit events are recorded.

The following configuration instances are defined by the configuration definition "sas.audit.record":

 Filter

GUID: 07333ea7-2fe9-48ae-ac0a-16e9a3aeda57
The globally unique identifier for the configuration instance.

Services: Audit service
Service to which this configuration instance applies.

application:

Customizable properties to control which application specific audit events are recorded.

`sas.audit.record.application.SASLogin.enabled:` true

`sas.audit.record.application.SASStudioV.enabled:` true

`sas.audit.record.application.SASVisualAnalytics.enabled:` true